

Material Safety Data Sheet



since 1895

NFPA	WHMIS	PPE	Transport Symbol
			Not regulated, non-bulk

Preparation Date 12/20/2006

Revision Date 04/21/2012

Revision Number 11

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Black-Knight™ Cold
Product Code 7343
UN-No 1999

Contact Manufacturer
 The Garland Company, Inc.
 3800 East 91st. Street
 Cleveland, Ohio 44105-2197
 Ph: (800) 762-8225 Fax: (216) 641-0633

Garland Canada, Inc.
 209 Carrier Drive
 Toronto, Ontario M9W 5Y8
 Ph: (416)747-7995 Fax: (416)747-1980

Emergency Telephone Number 1-800-762-8225 (24 Hrs.)

2. HAZARDS IDENTIFICATION

Emergency Overview

Combustible material
 Irritating to skin

Appearance Black.

Physical State Liquid.

Odor Petroleum distillates.

Mexico - Grade Moderate risk, Grade 2

Potential Health Effects

Principle Routes of Exposure Skin contact, Inhalation, Ingestion.

Acute Effects

Eyes Avoid contact with eyes. Irritating to eyes.
Skin Avoid contact with skin. Irritating to skin. May cause sensitization by skin contact.
Inhalation Avoid breathing vapors or mists. Irritating to mucous membranes. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects Prolonged exposure may cause chronic effects.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Skin disorders. Central nervous system.

Interactions with Other Chemicals Not available

Potential Environmental Effects See Section 12 for additional Ecological information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Chemical Name	CAS-No	Weight %	North American Hazard Indicator
Talc (non-asbestiform)	14807-96-6	5 - 10	1
Refined Coal Tar Pitch	65996-93-2	60 - 100	1
Styrene Butadiene Polymer	9003-55-8	5 - 10	1
Cellulose Fiber	9004-34-6	1 - 5	1

4. FIRST AID MEASURES

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Remove and wash contaminated clothing before re-use.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Do not induce vomiting. Call a physician or Poison Control Center immediately.

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Hazardous Combustion Products Carbon monoxide, Carbon dioxide (CO₂), Hydrocarbons.

Explosion Data

Sensitivity to mechanical impact	No
Sensitivity to static discharge	Yes

Specific Hazards Arising from the Chemical

Combustible material. Thermal decomposition can lead to release of irritating gases and vapours.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

NFPA**Health 3****Flammability 2****Instability 0****6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions	Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Keep out of waterways.
Methods for Containment	Dam up
Methods for Cleaning Up	Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Keep in suitable and closed containers for disposal.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Ensure adequate ventilation.
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico
Talc (non-asbestiform)	TWA: 2 mg/m ³		TWA: 2 mg/m ³	TWA: 2 mg/m ³
Refined Coal Tar Pitch	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³	STEL: 0.03 mg/m ³ STEL: 0.015 ppm TWA: 0.02 mg/m ³ TWA: 0.002 mg/m ³
Cellulose Fiber	TWA: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³	STEL: 20 mg/m ³ TWA: 10 mg/m ³

Chemical Name	NIOSH IDLH
Talc (non-asbestiform)	1000 mg/m ³ containing no asbestos and <1% quartz
Refined Coal Tar Pitch	80 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Do not allow ventilation equipment to draw material odors indoors..

Personal Protective Equipment**Eye/face Protection**

Tightly fitting safety goggles.

Skin Protection

Long sleeved clothing. Boots. Lightweight protective clothing.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene Measures

When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Black	
Odor	Petroleum distillates	
Physical State	Liquid	
pH	Not available	
Flash Point	112°F / 44°C	
Method	Tag closed cup	
Autoignition Temperature	910°F / 488°C	
Boiling Point/Range	313°F / 156°C	
Freezing Point	Not available	
Flammability Limits in Air	Lower 0.5%	Upper 6.0%
Explosive Properties	Not available	
Oxidizing Properties	Not available	
Evaporation Rate	0.37 for solvent (ether = 1)	
Vapor Pressure	2.7 mmHg	
Vapor Density	4.2	
Specific Gravity	> 1	
Water Solubility	Miscible with water	
Volatiles	<30% by volume	
VOC Content	270 g/L	

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to Avoid	Open flames and intense heat.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO ₂). Hydrocarbons.
Possibility of Hazardous Reactions	Hazardous polymerization does not occur

11. TOXICOLOGICAL INFORMATION

Acute Toxicity**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrocarbon Solvent	8400 mg/kg Rat	2000 mg/kg Rabbit	3400 ppm Rat 4 h 5.2 mg/L Rat 4 h
Cellulose Fiber	5 g/kg Rat	2 g/kg Rabbit	5800 mg/m ³ Rat 4 h

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA	Mexico
Refined Coal Tar Pitch	A1	Group 1	Known	X	A1

12. ECOLOGICAL INFORMATION

Ecotoxicity

No information available.

Hydrocarbon Solvent**Water Flea Data**

Daphnia magna EC50=6.14 mg/L (48 h)

Persistence/Degradability

Not available

Bioaccumulation/ Accumulation

Not available

Mobility in Environmental Media

Not available

Refined Coal Tar Pitch

log Pow = 6.04

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

US EPA Waste Number

D001

14. TRANSPORT INFORMATION

DOT

UN-No

Not regulated, non-bulk
1999

Special Provisions

BULK> 119 gallon container: Tars, liquid, UN1999, PG III

TDG

Not regulated

MEX

Not regulated

ICAO

UN-No

Proper Shipping Name

Hazard Class

Packing Group

UN1999
Tars, liquid
3
III

14. TRANSPORT INFORMATION

Description	Tars, liquid, UN1999, PG III
--------------------	------------------------------

IATA

UN-No	UN1999
Proper Shipping Name	Tars, liquid
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	Tars, liquid, UN1999, PG III

IMDG/IMO

Proper Shipping Name	Tars, liquid
Hazard Class	3
UN-No	UN1999
Packing Group	III
EmS No.	F-E, S-E
Description	Tars, liquid, UN1999, PG III

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	CHINA	KECL	PICCS	AICS
Talc (non-asbestiform)	X	X	-	X	-	-	X	X	X	X
Refined Coal Tar Pitch	X	X	-	X	-	X	X	X	X	X
Hydrocarbon Solvent	X	X	-	X	-	-	X	X	X	X
Styrene Butadiene Polymer	X	X	-	-	-	X	X	X	X	X
Cellulose Fiber	X	X	-	X	-	X	X	X	X	X

TSCA	Complies
DSL	Complies
NDSL	Complies
EINECS	Does not Comply
ELINCS	Does not Comply
ENCS	Does not Comply
CHINA	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

USA**Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

State Regulations

California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Talc (non-asbestiform)	X	X	X		X
Refined Coal Tar Pitch	X	X	X	X	
Cellulose Fiber	X		X		X

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B3 Combustible liquid
D2A Very toxic materials

16. OTHER INFORMATION

Preparation Date 12/20/2006
Revision Date 04/21/2012
Revision Summary Canadian address update

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS