

Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • Single-Ply LVOC Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer • Firestone Building Products Company
250 West 96th Street
Indianapolis, IN 46260
United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

Manufacturer • (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP

- Flammable Liquids 2 - H225
- Aspiration 1 - H304
- Skin Irritation 2 - H315
- Eye Irritation 2 - H319
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
- EUH066

DSD/DPD

- Highly Flammable (F)
- Irritant (Xi)
- Harmful (Xn)
- R11, R36/38, R65, R66, R67

2.2 Label Elements

CLP

DANGER



- Hazard statements**
- H225 - Highly flammable liquid and vapour
 - H304 - May be fatal if swallowed and enters airways
 - H315 - Causes skin irritation
 - H319 - Causes serious eye irritation
 - H336 - May cause drowsiness or dizziness
 - EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - P233 - Keep container tightly closed.
 - P240 - Ground and/or bond container and receiving equipment.
 - P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - P242 - Use only non-sparking tools.
 - P261 - Avoid breathing mist/vapours/spray.
 - P264 - Wash thoroughly after handling.
 - P243 - Take precautionary measures against static discharge.
 - P271 - Use only outdoors or in a well-ventilated area.
 - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- P370+P378 - In case of fire: Use appropriate media for extinction.
 - P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 - P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P362 - Take off contaminated clothing and wash before reuse.
 - P332+P313 - If skin irritation occurs: Get medical advice/attention.
 - P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P337+P313 - If eye irritation persists: Get medical advice/attention.
 - P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 - P331 - Do NOT induce vomiting.
- Storage/Disposal**
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 - P235 - Keep cool.
 - P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



- Risk phrases**
- R11 - Highly flammable.
 - R36/38 - Irritating to eyes and skin.
 - R65 - Harmful: may cause lung damage if swallowed.
 - R66 - Repeated exposure may cause skin dryness or cracking.
 - R67 - Vapours may cause drowsiness and dizziness.
- Safety phrases**
- S9 - Keep container in a well ventilated place
 - S16 - Keep away from sources of ignition - No Smoking.
 - S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

2.3 Other Hazards

- CLP**
- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.
- DSD/DPD**
- According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

- OSHA HCS 2012**
- Flammable Liquids 2 - H225

Aspiration 1 - H304
 Skin Irritation 2 - H315
 Eye Irritation 2 - H319
 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335
 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Highly flammable liquid and vapour - H225
 - May be fatal if swallowed and enters airways - H304
 - Causes skin irritation - H315
 - Causes serious eye irritation - H319
 - May cause respiratory irritation - H335
 - May cause drowsiness or dizziness - H336

Precautionary statements

- Prevention**
- Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210
 - Keep container tightly closed. - P233
 - Ground and/or bond container and receiving equipment. - P240
 - Use explosion-proof electrical/ventilating/lighting/equipment. - P241
 - Use only non-sparking tools. - P242
 - Take precautionary measures against static discharge. - P243
 - Avoid breathing mist/vapours/spray. - P261
 - Wash thoroughly after handling. - P264
 - Use only outdoors or in a well-ventilated area. - P271
 - Wear protective gloves/protective clothing/eye protection/face protection. - P280
- Response**
- In case of fire: Use appropriate media for extinction. - P370+P378
 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340
 - Call a POISON CENTER or doctor/physician if you feel unwell. - P312
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. - P303+P361+P353
 - Take off contaminated clothing and wash before reuse. - P362
 - If skin irritation occurs: Get medical advice/attention. - P332+P313
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - P305+P351+P338
 - If eye irritation persists: Get medical advice/attention. - P337+P313
 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. - P301+P310
 - Do NOT induce vomiting. - P331
- Storage/Disposal**
- Store in a well-ventilated place. Keep container tightly closed. - P403+P233
 - Keep cool. - P235
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS



- Flammable Liquids - B2
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
1-Chloro-4-(trifluoromethyl) benzene	CAS:98-56-6 EINECS:202-681-1	30% TO 60%	Ingestion/Oral-Rat LD50 • 13 g/kg Inhalation-Rat LC50 • 22 g/m ³	EU DSD/DPD: Self Classified: R10, Xi, R36/38 EU CLP: Self Classified: Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319 OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2	NDA
Naphtha (petroleum), hydrotreated light	CAS:64742-49-0 EINECS:265-151-9	10% TO 40%	NDA	EU DSD/DPD: Annex VI, Table 3.2: Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65 EU CLP: Annex VI: Carc. 1B, H350; Muta. 1B, H340; Asp. Tox. 1, H304 OSHA HCS 2012: Asp. Tox. 1	Component contains less than 0.1% benzene. Carcinogen and mutagen classifications do not apply for EU agencies.
Acetone	CAS:67-64-1 EINECS:200-662-2	10% TO 40%	Inhalation-Rat LC50 • 50100 mg/m ³ 8 Hour(s) Ingestion/Oral-Rat LD50 • 5800 mg/kg	EU DSD/DPD: Annex VI, Table 3.2: F; R11 Xi; R36 R66 R67 EU CLP: Annex VI: Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3: Narc., H336; EUH066 OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2; STOT SE 3: Resp. Irrit.; STOT SE 3: Narc.	NDA

See Section 11 for Toxicological Information. See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do NOT induce vomiting. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed**Notes to Physician**

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures**5.1 Extinguishing media****Suitable Extinguishing Media**

- LARGE FIRES: Water spray, fog or alcohol-resistant foam.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media

- Do not use a direct stream of water.

5.2 Special hazards arising from the substance or mixture**Unusual Fire and Explosion Hazards**

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Vapor explosion hazard indoors, outdoors or in sewers. Many liquids are lighter than water. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Dried solids can burn and release toxic fumes and vapors.

Hazardous Combustion Products

- No data available

5.3 Advice for firefighters

- Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Cool fire exposed containers with water. Move containers from fire area if you can do it without risk.

Section 6 - Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures****Personal Precautions**

- Ventilate enclosed areas. Wear appropriate protective clothing. Do not touch or walk through spilled material.

Emergency Procedures

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) Keep out of low areas. Stay upwind. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
A vapor suppressing foam may be used to reduce vapors.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use clean non-sparking tools to collect absorbed material.
All equipment used when handling the product must be grounded.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Keep away from fire. Keep away from heat and sparks. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Use only in well ventilated areas. All equipment used when handling the product must be grounded. Bond and ground all transfer containers and equipment. Take precautionary measures against static charges. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near container. Do not eat, drink or smoke when using this product. After handling wash hands thoroughly.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Keep container tightly closed. Keep away from incompatible materials.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick
Acetone (67-64-1)	STELs	750 ppm STEL	750 ppm STEL; 1800 mg/m ³ STEL	500 ppm STEL	750 ppm STEL	750 ppm STEL; 1782 mg/m ³ STEL
	TWAs	500 ppm TWA	500 ppm TWA; 1200 mg/m ³ TWA	250 ppm TWA	500 ppm TWA	500 ppm TWA; 1188 mg/m ³ TWA
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec
Acetone (67-64-1)	STELs	1250 ppm STEL; 2970 mg/m ³ STEL	750 ppm STEL	1250 ppm STEL; 2970 mg/m ³ STEL	750 ppm STEL	1000 ppm STEV; 2380 mg/m ³ STEV
	TWAs	1000 ppm TWA; 2370 mg/m ³ TWA	500 ppm TWA	1000 ppm TWA; 2370 mg/m ³ TWA	500 ppm TWA	500 ppm TWAEV; 1190 mg/m ³ TWAEV
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Saskatchewan	Canada Yukon	NIOSH	OSHA	

Acetone (67-64-1)	TWAs	500 ppm TWA	1000 ppm TWA; 2400 mg/m ³ TWA	250 ppm TWA; 590 mg/m ³ TWA	1000 ppm TWA; 2400 mg/m ³ TWA
	STELs	Not established	1250 ppm STEL; 3000 mg/m ³ STEL	Not established	Not established

8.2 Exposure controls

Engineering Measures/Controls

- This material is designed to be used outdoors, in roofing applications. Good general ventilation should be used. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear appropriate eye/face protection for the job/activity.

Skin/Body

- Wear appropriate gloves for the job/activity.

Environmental Exposure Controls

- In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Amber liquid with characteristic odor.
Color	Amber	Odor	Characteristic
Odor Threshold	Data lacking		
General Properties			
Boiling Point	133 F(56.1111 C)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	1.01 Water=1	Density	8.42 lbs/gal
Water Solubility	Insoluble	Viscosity	Data lacking
Explosive Properties	Not explosive.	Oxidizing Properties:	Not an oxidizer.
Volatility			
Vapor Pressure	175 mmHg (torr) @ 20 C(68 F)	Vapor Density	Data lacking
Evaporation Rate	Data lacking	VOC (Vol.)	88.1 %
Flammability			
Flash Point	-4 F(-20 C)	UEL	13 %
LEL	2.6 %	Autoignition	Data lacking
Flammability (solid, gas)	Flammable Liquid.		
Environmental			

Octanol/Water Partition coefficient	Data lacking		
-------------------------------------	--------------	--	--

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Avoid flames, sparks, or other sources of ignition.

10.5 Incompatible materials

- No data available

10.6 Hazardous decomposition products

- Carbon monoxide, carbon dioxide, hydrocarbon, hydrogen chloride and other acid products of combustion.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
1-Chloro-4-(trifluoromethyl) benzene (30% TO 60%)	98-56-6	Acute Toxicity: orl-rat LD50:13 gm/kg; ihl-rat LC50:22 gm/m3; Multi-dose Toxicity: ihl-rat TCLo:500 ppm/6H/4W-I
Acetone (10% TO 40%)	67-64-1	Acute Toxicity: orl-rat LD50:5800 mg/kg; ihl-rat LC50:50100 mg/m3/8H; Irritation: eye-rbt 20 mg SEV; skn-rbt 395 mg open MLD; Reproductive: ihl-rat TCLo:11000 ppm (6-19D preg)

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Aspiration 1 OSHA HCS 2012 • Aspiration 1
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met

STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2

Route(s) of entry/exposure ● Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

- No data available

Skin

Acute (Immediate)

- Causes skin irritation.

Chronic (Delayed)

- Repeated exposure may cause skin dryness or cracking.

Eye

Acute (Immediate)

- Causes serious eye irritation.

Chronic (Delayed)

- No data available.

Ingestion

Acute (Immediate)

- Material may be aspirated into the lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

Chronic (Delayed)

- No data available.

Key to abbreviations

LC = Lethal Concentration

TC = Toxic Concentration

LD = Lethal Dose

SEV = Severe

MLD = Mild

Section 12 - Ecological Information

12.1 Toxicity

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3	III	NDA
TDG	UN1133	ADHESIVES	3	III	Potential Marine Pollutant
IMO/IMDG	UN1133	ADHESIVES	3	III	NDA
ADN	UN1133	ADHESIVES	3	III	NDA
ADR/RID	UN1133	ADHESIVES	3	III	NDA
IATA/ICAO	UN1133	Adhesives	3	III	NDA

14.6 Special precautions for user

- None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

- Acute, Chronic, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	No	No	No
Acetone	67-64-1	Yes	Yes	Yes
Naphtha (petroleum), hydrotreated light	64742-49-0	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
1-Chloro-4-(trifluoromethyl)	98-56-6	Yes	No	Yes	No	Yes

benzene						
Acetone	67-64-1	Yes	No	Yes	No	Yes
Naphtha (petroleum), hydrotreated light	64742-49-0	Yes	No	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	B2, D2B

Canada - WHMIS - Ingredient Disclosure List

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	1 %

Environment

Canada - 2004 NPRI (National Pollutant Release Inventory)

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada - 2005 NPRI (National Pollutant Release Inventory)

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada - CEPA - Greenhouse Gases Subject to Mandatory Reporting

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada - CEPA - Priority Substances List

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada - DWQ (Drinking Water Quality) - IMACs

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Other

Canada - Accelerated Reduction/Elimination of Toxics (ARET)

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada New Brunswick

Environment

Canada - New Brunswick - Ozone Depleting Substances - Schedule A

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Canada - New Brunswick - Ozone Depleting Substances - Schedule B

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Europe**Other****EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification**

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65
• Acetone	67-64-1	F; R11 Xi; R36 R66 R67

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	T R:45-46-65 S:53-45
• Acetone	67-64-1	F Xi R:11-36-66-67 S:(2)-9-16-26

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	P
• Acetone	67-64-1	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	S:53-45
• Acetone	67-64-1	S:(2)-9-16-26

United States**Labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

Environment**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
--	---------	------------

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	5000 lb final RQ; 2270 kg final RQ
U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - CERCLA/SARA - Section 313 - Emission Reporting		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Included in waste stream: F039
U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	
U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	
U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	0.28 mg/L (wastewater); 160 mg/kg (nonwastewater)

U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	

U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	waste number U002 (Ignitable waste)

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

United States - Pennsylvania**Labor****U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
--	---------	------------

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H226 - Flammable liquid and vapour
- H340 - May cause genetic defects.
- H350 - May cause cancer.
- R10 - Flammable.
- R36 - Irritating to eyes.
- R45 - May cause cancer.
- R46 - May cause heritable genetic damage.

Last Revision Date

- 11/March/2014

Preparation Date

- 11/January/2012

Disclaimer/Statement of Liability

- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No data available