Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name

XR Bonding Adhesive

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)

Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer

• Firestone Building Products Company

250 West 96th Street Indianapolis, IN 46260

United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer (800) 424-9300 - CHEMTREC

Manufacturer (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP

Flammable Liquids 2 - H225
 Eye Irritation 2 - H319

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

EUH066

DSD/DPD

Highly Flammable (F)

Irritant (Xi)

R11, R36, R66, R67

2.2 Label Elements

CLP

DANGER





Hazard statements . H225 - Highly flammable liquid and vapour

H319 - Căuses serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements

Prevention .

P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. P233 - Keep container tightly closed.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing mist/vapours/spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response •

P370+P378 - In case of fire: Use appropriate media for extinction.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 - Specific treatment, see supplemental first aid information. P362 - Take off contaminated clothing and wash before reuse.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Storage/Disposal .

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P235 - Keep cool.

P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD







Risk phrases . R11 - Highly flammable.

R36 - Irritating to eyes.

R66 - Repeated exposure may cause skin dryness or cracking.

R67 - Vapours may cause drowsiness and dizziness.

Safety phrases •

S9 - Keep container in a well ventilated place

S16 - Keep away from sources of ignition - No Smoking.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

2.3 Other Hazards

CLP

According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

Flammable Liquids 2 - H225 Skin Irritation 2 - H315 Eye Irritation 2 - H319

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

2.2 Label elements **OSHA HCS 2012**

DANGER





Hazard statements . Highly flammable liquid and vapour - H225

Causes skin irritation - H315

Causes serious eye irritation - H319 May cause respiratory irritation - H335 May cause drowsiness or dizziness - H336

Precautionary statements

Prevention • Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210

Keep container tightly closed. - P233

Ground and/or bond container and receiving equipment. - P240 Use explosion-proof electrical/ventilating/lighting/equipment. - P241

Use only non-sparking tools. - P242

Take precautionary measures against static discharge. - P243

Avoid breathing mist/vapours/spray. - P261 Wash thoroughly after handling. - P264

Use only outdoors or in a well-ventilated area. - P271

Wear protective gloves/protective clothing/eye protection/face protection. - P280

Response .

In case of fire: Use appropriate media for extinction. - P370+P378

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340

Call a POISON CENTER or doctor/physician if you feel unwell. - P312

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. - P303+P361+P353

Specific treatment, see supplemental first aid information. - P321 Take off contaminated clothing and wash before reuse. - P362 If skin irritation occurs: Get medical advice/attention. - P332+P313

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. - P305+P351+P338 If eye irritation persists: Get medical advice/attention. - P337+P313

Storage/Disposal .

Store in a well-ventilated place. Keep container tightly closed. - P403+P233 Keep cool. - P235

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

2.3 Other hazards

OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

Flammable Liquids - B2 Other Toxic Effects - D2A Other Toxic Effects - D2B

2.2 Label elements

WHMIS





Flammable Liquids - B2 Other Toxic Effects - D2A Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

			Composition		
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acetone	CAS:67-64-1 EINECS:200- 662-2	50% TO 100%	Inhalation-Rat LC50 • _50100 mg/m³ 8 Hour(s) Ingestion/Oral-Rat LD50 • 5800 mg/kg	EU DSD/DPD: Annex VI, Table 3.2: F; R11 Xi; R36 R66 R67 EU CLP: Annex VI: Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 OSHA HCS 2012: Flam. Liq. 2; Eye Irrit 2A; STOT SE 3: Resp. Irrit. & Narc.	NDA
4-Heptanone, 2,6- dimethyl-	CAS:108-83-8 EINECS:203- 620-1	2.5% TO 10%	Ingestion/Oral-Rat LD50 • 5750 mg/kg Skin-Rabbit LD50 • 16120 mg/kg	EU DSD/DPD: Annex VI, Table 3.2: R10 Xi; R37 EU CLP: Annex VI: Flam. Liq. 3, H226; STOT SE 3, H335 OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2	NDA
Zinc oxide	CAS:1314-13- 2 EINECS:215- 222-5	<= 2.5%	NDA	EU DSD/DPD: Annex VI, Table 3.2: N; R50-53 EU CLP: Annex VI: Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Not Classified	NDA

See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye

• In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

 Rinse mouth. Drink 1 - 2 glasses of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

All treatments should be based on observed signs and symptoms of distress in the

patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media . LARGE FIRES: Water spray, fog or alcohol-resistant foam.

SMALL FIRES: Dry chemical, CO2, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use a direct stream of water.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back. Dried solids can burn and release toxic fumes and vapors.

Hazardous Combustion Products

No data available

5.3 Advice for firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Cool fire exposed containers with water.

Move containers from fire area if you can do it without risk.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Ventilate enclosed areas. Wear appropriate protective clothing. Do not touch or walk through spilled material.

Emergency Procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) Keep out of low areas. Stay upwind. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.

A vapor suppressing foam may be used to reduce vapors.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use clean non-sparking tools to collect absorbed material.

All equipment used when handling the product must be grounded.

6.4 Reference to other sections

Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

• Keep away from fire. Keep away from heat and sparks. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Use only in well ventilated areas. All equipment used when handling the product must be grounded. Bond and ground all transfer containers and equipment. Take precautionary measures against static charges. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near container. Do not eat, drink or smoke when using this product. After handling wash hands thoroughly.

7.2 Conditions for safe storage, including any incompatibilities

Storage

• Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Keep container tightly closed. Keep away from incompatible materials.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

			Exposure Limits	/Guidelines			
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick	
	STELs	10 mg/m3 STEL (respirable fraction)	10 mg/m3 STEL (respirable)	10 mg/m3 STEL (respirable)	10 mg/m3 STEL (respirable fraction)	10 mg/m3 STEL (fume)	
Zinc oxide (1314-13-2)	TWAs	2 mg/m3 TWA (respirable fraction)	2 mg/m3 TWA (respirable)	2 mg/m3 TWA (respirable)	2 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, dust); 5 mg/m3 TWA (fume)	
4-Heptanone, 2,6- dimethyl- (108-83-8)	TWAs	25 ppm TWA	25 ppm TWA; 145 mg/m3 TWA	25 ppm TWA	25 ppm TWA	25 ppm TWA; 145 mg/m3 TWA	
Acetone	STELs	750 ppm STEL	750 ppm STEL; 1800 mg/m3 STEL	500 ppm STEL	750 ppm STEL	750 ppm STEL; 1782 mg/m3 STEL	
(67-64-1)	TWAs	500 ppm TWA	500 ppm TWA; 1200 mg/m3 TWA	250 ppm TWA	500 ppm TWA	500 ppm TWA; 1188 mg/m3 TWA	
		Ex	Exposure Limits/Guidelines (Con't.)				
	Result	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec	
	STELs	10 mg/m3 STEL (fume)	10 mg/m3 STEL (respirable fraction)	10 mg/m3 STEL (fume)	10 mg/m3 STEL (respirable)	10 mg/m3 STEV (fume)	
Zinc oxide (1314-13-2)	TWAs	5 mg/m3 TWA (fume); 5 mg/m3 TWA (dust, respirable mass); 10 mg/m3 TWA (total mass, dust)	2 mg/m3 TWA (respirable fraction)	5 mg/m3 TWA (fume); 5 mg/m3 TWA (dust, respirable mass); 10 mg/m3 TWA (total mass, dust)	2 mg/m3 TWA (respirable)	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust); 5 mg/m3 TWAEV (fume)	
4-Heptanone, 2,6-	STELs	38 ppm STEL; 220 mg/m3 STEL	Not established	38 ppm STEL; 220 mg/m3 STEL	Not established	Not established	

dimethyl- (108-83-8)	TWAs		pm TWA; 145 n3 TWA	25 ppm 7	ΓWA	25 ppm TWA mg/m3 TWA	; 145	25 ppm TWA		25 ppm TWAEV; 145 mg/m3 TWAEV
Acetone	STELs) ppm STEL; 2970 n3 STEL	750 ppm	STEL	1250 ppm ST 2970 mg/m3 S		750 ppm STEL		1000 ppm STEV; 2380 mg/m3 STEV
(67-64-1)	TWAs) ppm TWA; 2370 n3 TWA	500 ppm	TWA	1000 ppm TV mg/m3 TWA	VA; 2370	500 ppm TWA		500 ppm TWAEV; 1190 mg/m3 TWAEV
			Ex	posure	Limits/Gui	delines (Co	on't.)			
	Res	sult	Canada Saskatchew	an	Canada `	Yukon		NIOSH		OSHA
Zinc oxide	TW	As	2 mg/m3 TWA (duand fume, respira fraction)		5 mg/m3 TW. 30 mppcf TW 10 mg/m3 TV	/A (dust);	5 mg/m3 and fum	3 TWA (dust e)	15 n dust	g/m3 TWA (fume); ng/m3 TWA (total :); 5 mg/m3 TWA pirable fraction)
(1314-13-2)	STE	Ls	Not established		10 mg/m3 ST 20 mg/m3 ST		10 mg/m	n3 STEL (fume)	Not	established
	Ceil	ings	Not established		Not establish	ed	15 mg/m	n3 Ceiling (dust)	Not	established
4-Heptanone, 2,6-	TW	As	25 ppm TWA		25 ppm TWA mg/m3 TWA	; 150	25 ppm mg/m3 1	TWA; 150 TWA		ppm TWA; 290 m3 TWA
dimethyl- (108-83-8)	STE	Ls	Not established		25 ppm STEL mg/m3 STEL	.; 150	Not esta	blished	Not	established
Acetone	TW	As	500 ppm TWA		1000 ppm TV mg/m3 TWA	VA; 2400	250 ppm mg/m3 1	n TWA; 590 TWA		0 ppm TWA; 2400 m3 TWA
(67-64-1)	STE	Ls	Not established		1250 ppm ST mg/m3 STEL	EL; 3000	Not esta	blished	Not	established

8.2 Exposure controls

Engineering Measures/Controls

• This material is designed to be used outdoors, in roofing applications. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

 In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face Skin/Body

- Wear appropriate eye/face protection for the job/activity.
- Wear appropriate gloves for the job/activity.

Environmental Exposure Controls

 In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = $\frac{\text{Short Term Exposure Limits are based on 15-minute}}{\text{exposures}}$

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Brown liquid with a characteristic odor.
Color	Brown	Odor	Characteristic odor.
Odor Threshold	Data lacking		
General Properties	-	-	
Boiling Point	131 F(55 C)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	рН	Data lacking
Specific Gravity/Relative Density	0.882 Water=1	Water Solubility	Insoluble
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility		-	
Vapor Pressure	175 mmHg (torr) @ 68 F(20 C)	Vapor Density	Data lacking
Evaporation Rate	Data lacking	Volatiles (Vol.)	64 %
Flammability		-	
Flash Point	-2 F(-18.8889 C)	UEL	13 %
LEL	2.6 %	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental		-	
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

Avoid flames, sparks, or other sources of ignition.

10.5 Incompatible materials

Strong oxidizers, acids, and bases.

10.6 Hazardous decomposition products

Oxides of carbon and nitrogen.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
		Acute Toxicity: orl-rat LD50:5800 mg/kg; ihl-rat LC50:50100 mg/m3/8H;
Acetone (50% TO 100%)	67-64-1	Irritation: eye-rbt 20 mg SEV; skn-rbt 395 mg open MLD;

		Reproductive: ihl-rat TCLo:11000 ppm (6-19D preg)
4-Heptanone, 2,6-dimethyl- (2.5% TO 10%)	I IIIX-X'X-X	Acute Toxicity: orl-rat LD50:5750 mg/kg; skn-rbt LD50:16120 mg/kg; Irritation: eye-rbt 500 mg MLD; skn-rbt 500 mg open MLD
Zinc oxide (<= 2.5%)		Irritation: eye-rbt 500 mg/24H MLD; skn-rbt 500 mg/24H MLD; Reproductive: orl-rat TDLo:6846 mg/kg (1-22D preg)

,	
GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2

Route(s) of entry/exposure Potential Health Effects Inhalation

• Inhalation, Skin, Eye, Ingestion

Acute (Immediate)

• May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

No data available

Skin

Acute (Immediate)

Causes skin irritation.

Chronic (Delayed)

Repeated exposure may cause skin dryness or cracking.

Eye

Acute (Immediate)

Causes serious eye irritation.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)
Chronic (Delayed)

No data available

No data available.

Key to abbreviations

LC = Lethal Concentration

TC = Toxic Concentration

LD = Lethal Dose

SEV = Severe

MLD = Mild

Section 12 - Ecological Information

12.1 Toxicity

Material data lacking.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3		NDA
TDG	UN1133	ADHESIVES	3	II	Potential Marine Pollutant
IMO/IMDG	UN1133	ADHESIVES	3	II	NDA
ADN	UN1133	ADHESIVES	3	II	NDA
ADR/RID	UN1133	ADHESIVES	3	II	NDA
IATA/ICAO	UN1133	Adhesives	3	II	NDA

14.6 Special precautions for

None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not relevant.

Preparation Date: 11/January/2012 Revision Date: 11/March/2014

Code

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Fire

		State Righ	t To Know	
Component	CAS	MA	NJ	PA
4-Heptanone, 2,6- dimethyl-	108-83-8	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes

			Inventory			
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
4-Heptanone, 2,6- dimethyl-	108-83-8	Yes	No	Yes	No	Yes
Acetone	67-64-1	Yes	No	Yes	No	Yes
Zinc oxide	1314-13-2	Yes	No	Yes	No	Yes

Canada

4-Heptanone, 2,6-dimethyl-	108-83-8	B3
Acetone	67-64-1	B2, D2B
Zinc oxide Zinc oxide as Zinc compounds	1314-13-2	Uncontrolled product according to WHMIS classification criteria Not Listed
anada - WHMIS - Ingredient Disclosure List		
4-Heptanone, 2,6-dimethyl-	108-83-8	1 %
Acetone	67-64-1	1 %
Zinc oxide	1314-13-2	1 %
Zinc oxide as Zinc compounds		Not Listed

Environment Canada - CEPA - Priority Substances List • 4-Heptanone, 2,6-dimethyl• Acetone • Zinc oxide • Zinc oxide as Zinc compounds 108-83-8 Not Listed 67-64-1 Not Listed Not Listed Not Listed

Other Canada - Accelerated Reduction/Elimination of Toxics (ARET)	
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed

Canada New Brunswick

4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
Canada - New Brunswick - Ozone Depleting Substances - Schedule B		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
	101110	Not Listed
Zinc oxide	1314-13-2	NOT LISTED

Europe

Other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	R10 Xi; R37
Acetone	67-64-1	F; R11 Xi; R36 R66 R67
Zinc oxide	1314-13-2	N; R50-53
Zinc oxide as Zinc compounds		Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	10%<=C: Xi; R:37
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	Xi R:10-37 S:(2)-24
• Acetone	67-64-1	F Xi R:11-36-66-67 S:(2)-9-16- 26
Zinc oxide	1314-13-2	N R:50/53 S:60-61
Zinc oxide as Zinc compounds		Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	S:(2)-24
Acetone	67-64-1	S:(2)-9-16-26
Zinc oxide	1314-13-2	S:60-61
Zinc oxide as Zinc compounds		Not Listed

United States

Labor U.S OSHA - Process Safety Management - Highly Hazardous Chemical	s		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed	
Acetone	67-64-1	Not Listed	
• Zinc oxide	1314-13-2	Not Listed	

Zinc oxide as Zinc compounds	Not Listed
U.S OSHA - Specifically Regulated Chemicals	
 4-Heptanone, 2,6-dimethyl- 	108-83-8 Not Listed
Acetone	67-64-1 Not Listed
Zinc oxide	1314-13-2 Not Listed
 Zinc oxide as Zinc compounds 	Not Listed

Environment —		
U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
 4-Heptanone, 2,6-dimethyl- 	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	5000 lb final RQ; 2270 kg final RQ
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		1.0 % de minimis concentration (Chemical Category N982)
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
• 4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
• Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Append	dix VII	

4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Included in waste stream: F039
• Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.C. DODA (December Concernation & December Act). Concetituants for Detection N	A a mid a vim v	
U.S RCRA (Resource Conservation & Recovery Act) - Constituents for Detection M	_	Niet I iste d
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone Zinc oxide	67-64-1 1314-13-2	Not Listed
	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		NOT LISTED
U.S RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constitue	ents	
 4-Heptanone, 2,6-dimethyl- 	108-83-8	Not Listed
Acetone	67-64-1	
• Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universa	l Treatment St	andards
• 4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
• Acetone	67-64-1	0.28 mg/L (wastewater); 160 mg/kg (nonwastewater)
• Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water	Monitoring	
• 4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
• Acetone	67-64-1	Tot Liotod
• Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely To Characteristics	oxic Wastes &	Other Hazardous
4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	waste number U002 (Ignitable waste)
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed

United States - California

4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed
4-Heptanone, 2,6-dimethyl-Acetone	108-83-8 67-64-1	Not Listed Not Listed
Zinc oxide	1314-13-2	Not Listed
Zinc oxide as Zinc compounds		Not Listed

1314-13-2	Not Listed Not Listed	
108-83-8	Not Listed	
67-64-1	Not Listed	
1314-13-2	Not Listed	
	Not Listed	
108-83-8	Not Listed	
67-64-1	Not Listed	
1314-13-2	Not Listed	
	Not Listed	
108-83-8	Not Listed	
67-64-1	Not Listed	
1314-13-2	Not Listed	
	Not Listed	
	67-64-1 1314-13-2 108-83-8 67-64-1 1314-13-2 108-83-8 67-64-1	108-83-8 Not Listed 67-64-1 Not Listed 1314-13-2 Not Listed Not Listed Not Listed 67-64-1 Not Listed 1314-13-2 Not Listed 108-83-8 Not Listed 67-64-1 Not Listed 1314-13-2 Not Listed

United States - Pennsylvania

4-Heptanone, 2,6-dimethyl-	108-83-8	Not Listed
Acetone	67-64-1	
Zinc oxide	1314-13-2	(fume)
Zinc oxide as Zinc compounds		
I.S Pennsylvania - RTK (Right to Know) - Special Haz	zardous Substances	
J.S Pennsylvania - RTK (Right to Know) - Special Haz 4-Heptanone, 2,6-dimethyl-		Not Listed
	108-83-8	Not Listed Not Listed
4-Heptanone, 2,6-dimethyl-	108-83-8 67-64-1	

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Relevant Phrases (code & full text)

• H226 - Flammable liquid and vapour

H335 - May cause respiratory irritation

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

R10 - Flammable.

R37 - Irritating to respiratory system.

R50 - Very toxic to aquatic organisms.

R53 - May cause long-term adverse effects in the aquatic environment.

Last Revision Date • 11/March/2014

Preparation Date

Disclaimer/Statement of Liability

• 11/January/2012

• The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No data available