

Section 1 - Product and Company Identification

Hazard Label CAUTION label

Company Information

Johns Manville
Roofing Systems
P.O. Box 5108
Denver, CO 80127 USA

Telephone: 303-978-2000 8:00AM-5:00PM M-F
Internet Address: <http://www.jm.com>
Emergency: 800-424-9300 (Chemtrec, In English)

Trade Names: MBR® Cold Application Adhesive

Use: Used in adhering roofing plies, modified bitumen membranes and for aggregate surfacings. It can be used as a direct substitute for asphalt in all JM modified bitumen roof membrane specifications.

Section 2 - Hazards Identification

Emergency Overview

HMIS Ratings: Health = 1 Fire = 2 Reactivity = 0

Inhalation

Irritation of the upper respiratory tract, coughing, and congestion may occur in extreme exposures. Severe irritation of the mouth, nose, and throat, as well as signs of central nervous system depression (drowsiness, dizziness, headache), may occur upon inhalation of vapors or gases.

Skin

Drying of skin, dermatitis, and blistering may occur following prolonged exposures.

Ingestion

This product is not intended to be ingested under normal conditions of use. May be harmful if swallowed. May cause gastrointestinal irritation and disturbances. May cause effects similar to those for inhalation exposure. Aspiration into the lungs may cause lung inflammation and other lung injury.

Eyes

Irritation, redness, and burning in eyes may occur.

Primary Routes of Entry (Exposure)

Inhalation, skin, and eye contact.

Target Organs

Skin, eye, lungs, central nervous system (CNS), respiratory system, kidney, liver.

Medical Conditions Aggravated by Exposure

Pre-existing eye, skin, respiratory, central nervous system (CNS), liver and kidney diseases or conditions.

Section 3 - Composition/Information on Ingredients

CAS #	Component	Percent
8052-42-4	Asphalt	40-45
8052-41-3	Stoddard solvent (mineral spirits)	13-19
64742-95-6	Petroleum naphtha, light aromatic	2-4

General Product Description

Black liquid.

Section 4 - First Aid Measures

First Aid: Inhalation

If the affected person is having difficulty breathing, administer oxygen or apply artificial respiration and immediately contact a medical professional.

First Aid: Skin

Remove contaminated clothing. Wash exposed areas with soap and water. If irritation develops or persists, seek medical attention. Launder contaminated clothing before reuse.

First Aid: Ingestion

Product is not intended to be ingested or eaten. If this product is ingested, do not induce vomiting and seek medical attention immediately.

First Aid: Eyes

Flush eyes with large amounts of water until irritation subsides. If irritation persists, seek medical attention.

First Aid: Notes to Physician

Treatment for inhalation, skin contact, or ingestion should be symptomatic. Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias.

Section 5 - Fire Fighting Measures**Flash Point:** 105°F**Upper Flammable Limit (UFL):** 6**Auto Ignition:** No Data**Rate of Burning:** Not determined**General Fire Hazards**

CAUTION: Combustible liquid and vapor.

Keep away from heat, sparks, and flame. Material is highly volatile and readily gives off vapors which are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Keep container closed. Use with adequate ventilation.

Extinguishing Media

Carbon dioxide (CO₂), dry chemical.

Fire Fighting Equipment/Instructions

Use NIOSH-approved self-contained breathing apparatus operating in the pressure demand mode and full fire fighting protective clothing. Avoid inhalation of vapors.

Section 6 - Accidental Release Measures**Containment Procedures**

Remove all sources of ignition. Evacuate and ventilate spill area. Dam spill area with sand, earth, or other suitable absorbent. Prevent entry of material into sewers, other water sources, or land areas. Wear full protective clothing and respiratory protection during clean-up as required to maintain exposures below the applicable exposure limit. Shovel absorbed material into containers in well-ventilated area.

Clean-Up Procedures

Place in closable container for disposal.

Section 7 - Handling and Storage**Handling Procedures**

Use protective equipment as described in Section 8 of this safety data sheet when handling uncontained material. Handle in accordance with good industrial hygiene and safety practices.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Product should be kept in a cool and dry area in original packaging. Do not freeze.

Section 8 - Exposure Controls / Personal Protection**Exposure Guidelines****A: General Product Information**

Protective equipment should be provided as necessary to prevent inhalation of vapors, prolonged skin contact, and to keep exposure levels below the applicable exposure limits.

B: Component Exposure Limits**Asphalt (8052-42-4)**

ACGIH: 0.5 mg/m³ TWA (fume, inhalable fraction, as benzene soluble aerosol)

Stoddard solvent (mineral spirits) (8052-41-3)

OSHA: 500 ppm TWA; 2900 mg/m³ TWA

100 ppm TWA; 525 mg/m³ TWA

ACGIH: 100 ppm TWA

PERSONAL PROTECTIVE EQUIPMENT**Personal Protective Equipment: Eyes/Face**

Safety glasses with side shields, chemical goggles, or a face shield is required.

Personal Protective Equipment: Skin

Impervious gloves such as nitrile rubber should be used to help prevent excessive skin contact.

Personal Protective Equipment: Respiratory

A NIOSH approved respirator must be used if vapor concentrations exceed exposure limits.

Ventilation

Local exhaust or general dilution ventilation may be required to maintain exposures below the applicable exposure limits. The need for ventilation systems should be evaluated by a professional industrial hygienist, while the design of specific ventilation systems should be conducted by a professional engineer.

Personal Protective Equipment: General

Protective equipment should be provided as necessary to prevent irritation of the throat, eyes, and skin, and to keep exposures below the applicable exposure limits identified in Section 8.

Section 9 - Physical & Chemical Properties

Appearance:	Black	Odor:	Mild
Physical State:	Liquid	pH:	Not applicable
Vapor Pressure:	4.6 mm Hg (20°C/68°F)	Vapor Density:	4.8
Boiling Point:	320° F	Melting Point:	Not applicable
Solubility (H₂O):	Insoluble	Specific Gravity:	1.08-1.2
VOC:	178 g/L EPA Test Method 24		

Section 10 - Stability & Reactivity Information**Stability**

These products are not reactive.

Incompatibility

Strong acids, alkalis, and oxidizing agents

Hazardous Decomposition

May form carbon dioxide, carbon monoxide, halogenated hydrocarbons, nitrogen oxides, various hydrocarbons.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information**Acute Toxicity****A: General Product Information**

Vapors from this product may cause eye and upper respiratory irritation, dry throat and mouth, nausea, headache, dizziness, drowsiness, and coma in extreme cases. Prolonged exposures may lead to liver and kidney injury.

B: Component Analysis - LD50/LC50**Asphalt (8052-42-4)**

Oral LD50 Rat: >5000 mg/kg; Dermal LD50 Rabbit:>2000 mg/kg

Petroleum naphtha, light aromatic (64742-95-6)

Inhalation LC50 Rat: >5.2 mg/L/4H; Inhalation LC50 Rat:3400 ppm/4H; Oral LD50 Rat:8400 mg/kg; Dermal LD50 Rabbit:>2000 mg/kg

Component Carcinogenicity**Asphalt (8052-42-4)**

ACGIH: A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)

IARC: Group 3 - Not Classifiable (IARC Supplement 7 [1987], Monograph 35 [1985] (steam-refined cracking-residue and air-refined))

Chronic Toxicity

Asphalt (asphalt CAS # 8052-42-4 and oxidized asphalt 64742-93-4; bitumens): In 1985/87, IARC (International Agency for Research on Cancer) concluded the following: (a) Bitumens are not classifiable as to their carcinogenicity to humans (Group 3). (b) Extracts of steam- and air-refined bitumens are possibly carcinogenic to humans (Group 2B). IARC found that evidence for carcinogenicity from animal studies was: inadequate for undiluted air-refined bitumens; limited for steam-refined and cracking-residue bitumens; sufficient for extracts of steam-refined and air-refined bitumen. IARC found that human evidence for carcinogenicity of asphalt fumes was inadequate. Studies of roofers indicated an excess of cancers; however, IARC concluded that, since roofers may be exposed also to coal-tar pitches and other materials, "the excess cancer risk cannot be attributed specifically to bitumens." In 1994, a published review of 20 epidemiology studies of asphalt workers and roofers agreed with IARC, that current human evidence is inadequate for the carcinogenicity of asphalt fumes in humans. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be released upon excessive heating, which results in thermal cracking of the asphalt compounds. Some of these PAHs have been identified as having the potential to induce carcinogenic and reproductive health effects.

Section 12 - Ecological Information**Ecotoxicity****A: General Product Information**

No data available for this product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity**Petroleum naphtha, light aromatic (64742-95-6)**

96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L

48 Hr EC50 Daphnia magna: 6.14 mg/L

Section 13 - Disposal Considerations**US EPA Waste Number & Descriptions****A: General Product Information**

This product is not expected to be a hazardous waste when it is disposed of according to the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Product characterization after use is recommended to ensure proper disposal under federal and/or state requirements.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transport Information**International Transport Regulations**

DOT: Not hazardous for ground transport.

350 gallon/BULK only:

UN1999, Tars, Liquid, 3, PG III

Flammable Liquid Label Required

IATA & IMDG: Contact JM Product Stewardship for classification and label.

Section 15 - Regulatory Information**US Federal Regulations****A: General Product Information**

SARA 311 Status. The following SARA 311 designations apply to this product: Immediate (acute) health hazard. Delayed (chronic) health hazard.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations**A: General Product Information**

Other state regulations may apply. Check individual state requirements.

Asphalt fumes may contain trace amounts of the following California Proposition 65 Listed Substances as known to the state of California to cause cancer or reproductive effects: Poly nuclear aromatic hydrocarbons (benz(a)anthracene, benzo(b)fluoranthene, benzo(j)fluoranthene, benzo(k)fluoranthene, benzo(a)pyrene).

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
Asphalt	8052-42-4	Yes	No	Yes	Yes	Yes	Yes
Stoddard solvent (mineral spirits)	8052-41-3	Yes	No	Yes	Yes	Yes	Yes

A: TSCA Status

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

B: Component Analysis - Inventory

Component	CAS #	TSCA	DSL	EINECS
Asphalt	8052-42-4	Yes	Yes	Yes
Stoddard solvent (mineral spirits)	8052-41-3	Yes	Yes	Yes
Petroleum naphtha, light aromatic	64742-95-6	Yes	Yes	Yes

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Stoddard solvent (mineral spirits)	8052-41-3	1 %

WHMIS Classification

Controlled Product Classification: B3 D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations. This SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Other Information

Prepared for:
Johns Manville
Roofing Systems
P. O. Box 5108
Denver, CO USA 80217-5108

Prepared by:
Johns Manville Technical Center
P.O. Box 625005
Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Date	MSDS #	Reason
08/21/08	3165-1.0000	Moved product from SDS 3117

End of Sheet 3165