

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)
 PRS Glass Ply VI

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section 1

Manufacturer's Name
 DERBIGUM Americas, Inc.

Emergency Telephone Number
 800-727-9872

Address (Address, Street, City, State, and ZIP Code)
 4821 Chelsea Ave.

Telephone Number for Information
 800-727-9872

Kansas City, MO 64130

Date Prepared
 March 18, 2011

Signature of Preparer (Optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	CAS NO.	ACGIH TLV	Other Limits Recommended	% (optional)
Roofing Sheet composed of:				
Petroleum Asphalt	8052-42-4		5mg/m3*	
Fiberglass Mat			Not established	
Sand Dusting	14808-60-7		10 mg/m3	

* As Fumes

Section III - Physical / Chemical Characteristics

Unstabilized Asphalt Coating

Boiling Point	NA	Specific Gravity (H ₂ O =1)	VAR
Vapor Pressure (mm Hg.)	NA	Melting Point	>200°F
Vapor Density (AIR=1)	NA	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Nil		

Appearance and Odor Thin, black non-woven sheet, with asphalt odor

Section IV - Fire and explosion Hazard Data

Flash Point (Method Used) Cleveland Open Cup 450°F	Flammable Limits Unknown	LEL N/A	UEL N/A
Extinguishing Media	Use water spray, dry chemical foam, or CO ₂		
Special Fire Fighting Procedures	Water or foam may cause frothing. Use water to keep fire exposed containers cool. Wear self contained breathing apparatus.		
Unusual Fire and Explosion Hazards	CO and other hazardous vapors may be a product of combustion.		

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	N/A under normal warehouse storage
Incompatibility (Materials to avoid)		Hydrofluoric Acid	
Hazardous Decomposition or Byproducts		Co ₁ Co ₂ , fumes, smoke	
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Yes-During heat application of product generating asphalt fumes.			
Health Hazards (Acute and Chronic)		Acute: Nose and throat irritation. May cause dizziness.	
		Chronic: There are no studies indicating asphalt causes cancer or respiratory damage in man.	
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure		Nose and throat, eye irritation	
Medical Conditions Generally Aggravated by Exposure		None Known	

Emergency and First Aid Procedures Remove individual to fresh air. If irritation persists, seek medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	
sources, provide	Keep material dry, do not use or handle near ignition
	adequate ventilation. Use good housekeeping
Waste Disposal Method regulations.	Dispose of in accordance with local, state and federal
Precautions to Be Taken in Handling and Storing	Keep material dry.

Other Precautions

Section VIII - Control Measures

Respiratory Protection (Specify Type)		Respirator or dust mask is recommended.	
Ventilation	Local Exhaust	Special	None
	Mechanical (General)	N/A	Other
Protective Gloves	Yes	Eye Protection recommended	Goggles or safety glasses
Other Protective Clothing or Equipment	Long sleeve shirt, trousers, smooth bottom work shoes.		

