

## SAFETY DATA SHEET

### 1. Identification

**Material name:** SOLARGARD SEAM SEALER 2 GAL  
**Material:** 151102C

**Recommended use and restriction on use**

**Recommended use:** Sealant  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco U.S. Roofing  
3735 Green Road  
Cleveland OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:** 216-292-5000  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

### 2. Hazard(s) identification

**Hazard Classification**

**Health Hazards**

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

**Unknown toxicity - Health**

Acute toxicity, oral	55.2 %
Acute toxicity, dermal	63.75 %
Acute toxicity, inhalation, vapor	99.89 %
Acute toxicity, inhalation, dust or mist	94.37 %

**Environmental Hazards**

Acute hazards to the aquatic environment	Category 3
------------------------------------------	------------

**Unknown toxicity - Environment**

Acute hazards to the aquatic environment	88.81 %
Chronic hazards to the aquatic environment	100 %

**Label Elements**

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.  
May cause cancer.  
Harmful to aquatic life.

**Precautionary Statement:**

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:** If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	15 - 40%
Polyvinyl chloride	9002-86-2	15 - 40%
Titanium dioxide	13463-67-7	3 - 7%
Petroleum distillates	64742-47-8	3 - 7%
Calcium oxide	1305-78-8	1 - 5%
Xylene	1330-20-7	1 - 5%
Amorphous silica	7631-86-9	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Nonane	111-84-2	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

<b>Ingestion:</b>	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
<b>Inhalation:</b>	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
<b>Skin Contact:</b>	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
<b>Eye contact:</b>	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

#### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Methods and material for containment and cleaning up:**

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:**

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

**Precautions for safe handling:**

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

**Conditions for safe storage, including any incompatibilities:**

Store locked up.

## 8. Exposure controls/personal protection

**Control Parameters**

**Occupational Exposure Limits**

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)

Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWAEV	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWAEV	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Calcium oxide	TWA	2 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

### Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

### Individual protection measures, such as personal protective equipment

**General information:** Use personal protective equipment as required.

**Eye/face protection:** Wear goggles/face shield.

#### Skin Protection

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

**Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

## 9. Physical and chemical properties

### Appearance

**Physical state:** solid

**Form:** Paste

**Color:** White

**Odor:** Mild

**Odor threshold:** No data available.

**pH:** No data available.

**Melting point/freezing point:** No data available.

**Initial boiling point and boiling range:** No data available.

**Flash Point:** > 93 °C > 199 °F (Setaflash Closed Cup)

<b>Evaporation rate:</b>	Slower than n-Butyl Acetate
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.3
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of Hazardous Reactions:</b>	No data available.
<b>Conditions to Avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	Causes mild skin irritation. May cause an allergic skin reaction.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

**Oral**  
**Product:** ATEmix: 168,265.62 mg/kg

**Dermal**  
**Product:** ATEmix: 14,945.46 mg/kg

**Inhalation**  
**Product:** No data available.

**Repeated dose toxicity**  
**Product:** No data available.

**Skin Corrosion/Irritation**  
**Product:** No data available.

**Serious Eye Damage/Eye Irritation**  
**Product:** No data available.

**Specified substance(s):**

Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Petroleum distillates	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Calcium oxide	in vivo (Rabbit, 24 hrs): Category 1
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Amorphous silica	in vivo (Rabbit, 24 hrs): Not irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
Ethylbenzene	Irritating
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Nonane	in vivo (Rabbit, 24 - 72 hrs): Not irritating

**Respiratory or Skin Sensitization**

**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause sensitization by inhalation.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.
------------------------------------------	-------------------------------

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

Polyvinyl chloride	Cancer
--------------------	--------

**Germ Cell Mutagenicity**

<b>In vitro</b> Product:	No data available.
-----------------------------	--------------------

<b>In vivo</b> Product:	No data available.
----------------------------	--------------------

<b>Reproductive toxicity</b> Product:	No data available.
------------------------------------------	--------------------

<b>Specific Target Organ Toxicity - Single Exposure</b> Product:	No data available.
---------------------------------------------------------------------	--------------------

<b>Specific Target Organ Toxicity - Repeated Exposure</b> Product:	No data available.
-----------------------------------------------------------------------	--------------------

<b>Aspiration Hazard</b> Product:	No data available.
--------------------------------------	--------------------

<b>Other effects:</b>	No data available.
-----------------------	--------------------

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:**

<b>Fish</b> Product:	No data available.
-------------------------	--------------------

**Specified substance(s):**

Titanium dioxide	LC 50 (Mummichog ( <i>Fundulus heteroclitus</i> ), 96 h): > 1,000 mg/l Mortality
Petroleum distillates	LC 50 (Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> ), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow ( <i>Pimephales promelas</i> ), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> ), 24 h): 11 - 18 mg/l Mortality

**Aquatic Invertebrates****Product:** No data available.**Specified substance(s):**

Titanium dioxide	EC 50 (Water flea ( <i>Daphnia magna</i> ), 48 h): > 1,000 mg/l Intoxication
Xylene	LC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.53 - 3.17 mg/l Intoxication

**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**

Titanium dioxide	LC 0 ( <i>Coregonus autumnalis migratorius</i> G., 30 d): 3 mg/l experimental result
Petroleum distillates	NOAEL ( <i>Oncorhynchus mykiss</i> , 28 d): 0.098 mg/l QSAR
Calcium oxide	NOAEL ( <i>Oncorhynchus mykiss</i> , 60 d): 307 mg/l interpreted
Xylene	NOAEL ( <i>Oncorhynchus mykiss</i> , 56 d): > 1.3 mg/l experimental result
Aluminum oxide	NOAEL ( <i>Pimephales promelas</i> , 28 d): 4.7 mg/l experimental result
Hydrotreated heavy naphthenic distillate	NOAEL ( <i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
Nonane	NOAEL ( <i>Oncorhynchus mykiss</i> , 28 d): 0.252 mg/l QSAR

**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.

**Persistence and Degradability**

**Biodegradation Product:** No data available.

**BOD/COD Ratio Product:** No data available.

**Bioaccumulative Potential  
Bioconcentration Factor (BCF)**

**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow) Product:** No data available.

**Specified substance(s):**  
Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Nonane Log Kow: 5.46

**Mobility in Soil:** No data available.

**Other Adverse Effects:** Harmful to aquatic organisms.

**13. Disposal considerations**

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

**14. Transport information****TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**15. Regulatory information****US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard categories**Delayed (Chronic) Health Hazard  
Immediate (Acute) Health Hazards**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.



**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium Carbonate (Limestone)	500 lbs
Polyvinyl chloride	500 lbs
Titanium dioxide	500 lbs
Petroleum distillates	500 lbs
Calcium oxide	500 lbs
Xylene	500 lbs
Amorphous silica	500 lbs
Aluminum oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Nonane	500 lbs

**SARA 313 (TRI Reporting)**Chemical Identity

Xylene  
Ethylbenzene

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations****US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity

Calcium Carbonate (Limestone)  
Polyvinyl chloride  
Titanium dioxide  
Petroleum distillates  
Calcium oxide  
Xylene

**US. Massachusetts RTK - Substance List**Chemical Identity

Calcium Carbonate (Limestone)  
Titanium dioxide  
Petroleum distillates  
Calcium oxide  
Xylene  
Isophorone Diisocyanate  
Crystalline Silica (Quartz)/ Silica Sand

**US. Pennsylvania RTK - Hazardous Substances****Chemical Identity**

Calcium Carbonate (Limestone)  
Titanium dioxide  
Petroleum distillates  
Calcium oxide  
Xylene

**US. Rhode Island RTK****Chemical Identity**

Xylene

**Other Regulations:**

<b>Regulatory VOC (less water and exempt solvent):</b>	82 g/l
<b>VOC Method 310:</b>	6.33 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

<b>16. Other information, including date of preparation or last revision</b>
------------------------------------------------------------------------------

**Revision Date:** 08/05/2015

**Version #:** 1.0

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

